

Mechanically joined keylock every six inches makes Arden Architectural's standard grates the strongest grates of their type on the market. UltraSorb® tread stands up to heavy traffic and absorbs more than three times the dirt and moisture as standard carpet. UltraSorb treads are recommended for interior use. This product carries a five-year warranty.


DETAIL NOTES:

- 1 - Tread rails must run perpendicular to traffic direction.
- 2 - Dimensions in the traffic direction can only be changed in 1-1/2" (38.1mm) increments unless aluminum filler is attached to the frame.
- 3 - Grate dimensions allow for clearance between grate sections and frames in the width dimension.

SPECIFICATION:

GrateDesign Model G-100U UltraSorb tread grate by Arden Architectural Specialties, Inc.; with 1-3/4" (44.5mm) deep, 6063-T52 aluminum alloy rails, with treads of 100% polyamide fibers, 80 d'tex and 40 d'tex, tufted, class 1 fire rated; spaced 1-1/2" (38.1mm) o.c.; with keylocks spaced [6" (152.4mm)][3" (76.2mm) o.c.]; use with [level-bed type F-1][type F-LANG large angle][deep-pit type F-2][type F-2T thin slab]frame.

Complete specifications available on our website at www.ardenarch.com.

CUST. ORDER #	ARCHITECT			 Arden Architectural Specialties, Inc.™ 151 FIFTH AVE. NW SUITE J ST. PAUL, MN 55112-3268 TOLL-FREE 800.521.1826 TEL 651.631.1607 FAX 651.631.0251
CUSTOMER	CONTRACTOR			
PROJECT	RAIL MODEL G-100U	FRAME MODEL N/A	SCALE NTS	