

Mechanically joined keylock every six inches makes Arden Architectural's standard grates the strongest grates of their type on the market. Optional three-inch spacing is available for grates in areas with heavy rolling loads. Buffed-rubber treads stand up to years of heavy wear, even in extremely high traffic areas. This product carries a five-year warranty.


DETAIL NOTES:

- 1 - Tread rails must run perpendicular to traffic direction.
- 2 - Traffic direction dimension can only be changed in 1-1/2" (38.1mm) increments unless aluminum filler is attached to the frame.
- 3 - Grate dimensions allow for clearance between grate sections and frames in the width dimension.

SPECIFICATION:

Model G-285 ENVIRONtread® grate by Arden Architectural Specialties, Inc.; with 1-3/4" (44.5mm) deep, 6063-T52 aluminum alloy rails, spaced 1-1/2" (38.1mm) o.c.; with two buffed-rubber treads per rail; with keylocks spaced [6"(152.4mm)][3"(76.2mm)] o.c.; use with aluminum [type F-1 level-bed][type F-LANG large angle][type F-2 deep pit][type F-2T thin slab] frame.

Complete specifications available on our website at www.ardenarch.com.

CUST. ORDER #		ARCHITECT		 Arden Architectural Specialties, Inc.™ 151 FIFTH AVE. NW SUITE J ST. PAUL, MN 55112-3268 TOLL-FREE 800.521.1826 TEL 651.631.1607 FAX 651.631.0251
CUSTOMER		CONTRACTOR		
PROJECT	RAIL MODEL G-285	FRAME MODEL N/A	SCALE NTS	